

NEW POOL OWNERS LIST OF HELPFUL HINTS

CHEMICAL BALANCE

TEST YOUR **PH** BALANCE AT LEAST TWICE A WEEK AND ADJUST IT ACCORDING TO THE TEST RESULTS. ONCE THE PLASTER HAS COMPLETED CURING THE TESTING OF **PH** BALANCE IS REQUIRED ONE TIME PER WEEK. SEE THE BIO GUARD CHEMICAL BOOK FOR DETAILS.

FILTRATION SYSTEM

OPERATE YOUR POOL FILTRATION SYSTEM FOR (12) HOURS PER DAY

HIGH PRESSURE- IS A PROBLEM AT OR AFTER THE FILTER
RESOLVE PROBLEM BY BACKWASHING

LOW PRESSURE- IS A PROBLEM AT OR BEFORE THE PUMP
RESOLVE PROBLEM

- 1) CHECK THE WATER LEVEL – MAKE SURE IT IS FLOWING THROUGH THE SKIMMER BOX
- 2) CHECK THE SKIMMER BASKETS – MAKE SURE THEY ARE CLEAR OF DEBRIS
- 3) CHECK THE WEIR DOOR – MAKE SURE IT IS MOVING FREELY AND OPENS ALL THE WAY DOWN
- 4) CHECK THE PUMP BASKET AT THE EQUIPMENT – MAKE SURE IT IS CLEAN AND EMPTY OF DEBRIS

NO PRESSURE-THE POOL PUMP HAS LOST ITS PRIME
CAUSED BY LOW WATER LEVEL OR CLOGGED BASKETS

RESOLVE PROBLEM

CLEAN OUT THE BASKETS – RAISE THE WATER LEVEL - FORCE PRIME THE PUMP

- SHUT OFF EQUIPMENT
- OPEN THE PUMP LID
- CLEAN OUT THE BASKET
- RESET BASKET
- FILL PUMP HOUSING WITH WATER UNTIL OVERFLOWING ROUGHLY ONE MINUTE
- QUICKLY REPLACE THE PUMP LID AND TIGHTEN
- TURN EQUIPMENT ON
- PRESSURE SHOULD BE NORMAL

POLARIS AUTOMATIC POOL CLEANER

THE POLARIS POOL CLEANER HAS IT'S OWN TIME CLOCK AND SHOULD BE SET TO RUN FOR ROUGHLY 3 TO 4 HOURS PER DAY. THE POLARIS CLEANER SHOULD ALWAYS BE OPERATED WITHIN THE FILTRATION CYCLE FOR MAXIMUM EFFICIENCY.